JBC

The Soldering Co.

Nano Stations

When the highest precision is your priority

For applications requiring the highest precision

- The best solution for soldering and desoldering very small-sized components such as chips 01005, 0201, 0402, etc.



The most exceptional technology

- JBC has become the best choice for electronics professionals.
- See for yourself JBC Exclusive Heating System and its outstanding thermal performance.

TFT screen

The menu is **intuitive and easy to use** thanks to the improved interface usability. It allows you to personalize over 20 parameters to help manage the soldering process. Set temperature limits, check usage counters, lock the station parameters with a PIN or program **Sleep & Hibernation Modes**.
The working screen shows the **selected tool** with its corresponding port, the working temperature of the tip and the **power** indicator at a glance.

Cleaning & extraction set (x2)

It consists of a **Tip Cleaning Stand** and a **Quick Cartridge Extractor** which can be used single-handedly.
Each set can accommodate a different cleaning system and allows you to organize cartridges according to the job. This means you **save time** and **increase productivity.**
The cleaning system is **replaceable** and can be easily emptied.

Intelligent Heat Management

When the tool is placed back in the stand, **Hibernation Mode** is automatically activated. The power is cut off and the tip cools down to room temperature, **increasing tip life by more than 5 times.**

Precision tools

NT115 Nano Handle and **AN115 Adjustable Nano Tweezers** are light and ergonomic.
The short-distance tip-to-grip ensures greater precision.

C115 Cartridges for Nano Tools

CONICAL



C115126 C115101 C115103 C115106 C115107

CONICAL BENT



C115124 C115118 C115105 C115110

BEVEL



C115109 C115127

CHISEL



C115116 C115117 C115108 C115125 C115113 C115114

CONFORMAL COATING REMOVAL



C115115

SPOON

C115128

KNIFE



C115112 C115120

BLADE



C115111

HIGH THERMAL PERFORMANCE



C115213 C115221 C115222



C115214 C115223 C115212 C115211

mm (in)

Stations Communication

Nano Stations incorporate different connectors on the back to share data with other devices. **Increase your working possibilities.**

USB-A Port
By using a USB flash drive, you can update the latest software (available on **www.jbctools.com**), extract graphs.

USB-B Port
The user can monitor and manage parameters of several stations from one PC (e.g. graphs of the work process). It is necessary to download JBC Software (available on **www.jbctools.com**) and install it onto the PC.

ROBOT Connector
Use this port to connect the station with a JBC Fume Extractor in order to automatically activate extraction when the tools are in use.
Remotely control the station using an RS-232 connection with JBC Robot protocol.

P405 or P005 Pedal
Make the tool enter Hibernation or Sleep Mode by pushing down the pedal. This way you cause no thermal stress when placing the component onto PCB with the Nano Tweezers.

Specifications

Dimensions	170 x 90 x 135 mm / 6.69 x 3.54 x 5.31 in
Weight	2.5 Kg / 5.4 lb
Ref. - Voltage (AC)	**NASE-9C / NANE-9C** - 100V 50/60Hz **NASE-1C / NANE-1C** - 120V 50/60Hz **NASE-2C / NANE-2C** - 230V 50/60Hz
Ouput peak power	14 W per tool
Operating room temp.	10 - 50 ºC / 50 - 122 ºF

Temperature range	90 - 450 ºC / 190 - 840 ºF
Idle Temp. Stability (still air)	± 1.5 ºC (± 3 ºF) / Meets and exceed IPC J-STD-001F
Tip to ground voltage / resistance	Meets and exceed ANSI/ESD S20.20-2014 IPC J-STD-001F
Connections	USB-A / USB-B / Pedal / RJ12 for Robots